

14438

SAFETY DATA SHEET

GHS

United States

Section 1. Product and company identification

Product name DARVAN® 670 In case of emergency

1-203-295-2140

Code Chemtrec: 1-800-424-9300

> Outside US: +1-703-527-3887

33 Winfield Street Norwalk, CT 06855

Vanderbilt Minerals, LLC

Chemical name Sodium salt of naphthalene sulfonate polymerized with formaldehyde.

Sodium salt of poly-naphthalene sulfonic acid. Synonym

Material uses Dispersing agent.

Powder. **Product type**

Supplier/Manufacturer

Section 2. Hazards identification

OSHA/HCS status This material is considered hazardous by the OSHA Hazard Communication Standard

(29 CFR 1910.1200).

Classification of the COMBUSTIBLE DUSTS

substance or mixture

Percentage of the mixture consisting of ingredient(s) of unknown toxicity: 12.5%

GHS label elements

Signal word Warning

Hazard statements May form combustible dust concentrations in air.

Precautionary statements

Prevention Not applicable. Response Not applicable. Not applicable. **Storage Disposal** Not applicable.

Supplemental label Keep container tightly closed. Keep away from heat, hot surfaces, sparks, open flames

and other ignition sources. No smoking. Prevent dust accumulation.

elements

Hazards not otherwise Fine dust clouds may form explosive mixtures with air. Handling and/or processing of this material may generate a dust which can cause mechanical irritation of the eyes, classified

skin, nose and throat.

11/27/2017 Validation date 3/7/2019 Date of previous issue 1/13

Section 3. Composition/information on ingredients

Substance/mixture

Mixture

Ingredient name	CAS number	% by weight
sodium polynaphthalenesulfonate	9084-06-4	80 - 94
sodium sulfate	7757-82-6	1 - 12
water	7732-18-5	4 - 8
formaldehyde	50-00-0	<0.1
quinoline	91-22-5	<0.09
naphthalene	91-20-3	<0.03

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact Immediately flush eyes with plenty of water, occasionally lifting the upper and lower

eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10

minutes. Get medical attention if irritation occurs.

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. If

not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar,

tie, belt or waistband.

Skin contact Flush contaminated skin with plenty of water. Remove contaminated clothing and

shoes. Get medical attention if symptoms occur. Wash clothing before reuse. Clean

shoes thoroughly before reuse.

Ingestion Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and

keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately.

Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye contact Exposure to airborne concentrations above statutory or recommended exposure limits

may cause irritation of the eyes.

Inhalation Exposure to airborne concentrations above statutory or recommended exposure limits

may cause irritation of the nose, throat and lungs.

Skin contact

No known significant effects or critical hazards.

Ingestion

No known significant effects or critical hazards.

Over-exposure signs/symptoms

Eye contact Adverse symptoms may include the following:

irritation redness

Validation date : 3/7/2019 Date of previous issue : 11/27/2017 2/13

Section 4. First aid measures

Inhalation Adverse symptoms may include the following:

respiratory tract irritation

coughing

Skin contact No specific data.

Ingestion No specific data.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician Treat symptomatically. Contact poison treatment specialist immediately if large

quantities have been ingested or inhaled.

Specific treatments No specific treatment.

Protection of first-aidersNo action shall be taken involving any personal risk or without suitable training. It may

be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing

media

Do not use water jet.

Unsuitable extinguishing media

modiu

Specific hazards arising

Fine dust clouds may form explosive mixtures with air.

Hazardous thermal

from the chemical

decomposition products

Decomposition products may include the following materials:

In case of fire, use water spray (fog), foam, dry chemical or CO₂.

carbon dioxide carbon monoxide sulfur oxides metal oxide/oxides

Special protective actions

for fire-fighters

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water

spray to keep fire-exposed containers cool.

Special protective equipment for fire-fighters

Fire-fighters should wear appropriate protective equipment and self-contained breathing

apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing dust. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders

If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Section 6. Accidental release measures

Environmental precautions

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

Small spill

Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Vacuum or sweep up material and place in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor.

Large spill

Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Vacuum or sweep up material and place in a designated, labeled waste container. Avoid creating dusty conditions and prevent wind dispersal. Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures

Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing dust. Avoid the creation of dust when handling and avoid all possible sources of ignition (spark or flame). Prevent dust accumulation. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Electrical equipment and lighting should be protected to appropriate standards to prevent dust coming into contact with hot surfaces, sparks or other ignition sources. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Validation date : 3/7/2019 Date of previous issue : 11/27/2017 4/13

Section 8. Exposure controls/personal protection

Ingredient name	Exposure limits		
quinoline	AIHA WEEL (United States, 10/2011). Absorbed through skin.		
formaldehyde	TWA: 0.001 ppm 8 hours. ACGIH TLV (United States). TWA: 0.37 mg/m³ 8 hours. STEL: 2.5 mg/m³ 15 minutes. ACGIH TLV (United States, 6/2013). Skin sensitizer. C: 0.3 ppm C: 0.37 mg/m³ OSHA PEL 1989 (United States, 3/1989). TWA: 0.75 ppm 8 hours. STEL: 2 ppm 15 minutes. OSHA PEL Z2 (United States, 2/2013). TWA: 0.75 ppm 8 hours. STEL: 2 ppm 15 minutes. NIOSH REL (United States, 10/2013). TWA: 0.016 ppm 10 hours. CEIL: 0.1 ppm 15 minutes. OSHA PEL (United States, 2/2013). TWA: 0.75 ppm 8 hours.		
naphthalene	NIOSH REL (United States, 10/2013). TWA: 10 ppm 10 hours. TWA: 50 mg/m³ 10 hours. STEL: 15 ppm 15 minutes. STEL: 75 mg/m³ 15 minutes. ACGIH TLV (United States, 6/2013). Absorbed through skin. TWA: 10 ppm 8 hours. TWA: 52 mg/m³ 8 hours. STEL: 15 ppm 15 minutes. STEL: 79 mg/m³ 15 minutes. OSHA PEL 1989 (United States, 3/1989). TWA: 10 ppm 8 hours. TWA: 50 mg/m³ 8 hours. STEL: 15 ppm 15 minutes. STEL: 15 ppm 15 minutes. OSHA PEL (United States, 2/2013). TWA: 10 ppm 8 hours. TWA: 10 ppm 8 hours. TWA: 10 ppm 8 hours.		

Appropriate engineering controls

Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Validation date : 3/7/2019 Date of previous issue : 11/27/2017 5/13

Section 8. Exposure controls/personal protection

Hygiene measures Wash hands, forearms and face thoroughly after handling chemical products, before

eating, smoking and using the lavatory and at the end of the working period.

Appropriate techniques should be used to remove potentially contaminated clothing.

Wash contaminated clothing before reusing. Ensure that eyewash stations and safety

showers are close to the workstation location.

Eye/face protection Safety eyewear complying with an approved standard should be used when a risk

assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with sideshields. If operating conditions cause high dust concentrations to be produced, use

dust goggles. Recommended: safety glasses with side-shields

Skin protection

Hand protection Chemical-resistant, impervious gloves complying with an approved standard should be

worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the

protection time of the gloves cannot be accurately estimated.

Body protection Personal protective equipment for the body should be selected based on the task being

performed and the risks involved and should be approved by a specialist before

handling this product. Recommended: lab coat

Other skin protection Appropriate footwear and any additional skin protection measures should be selected

based on the task being performed and the risks involved and should be approved by a

specialist before handling this product.

Respiratory protectionUse a properly fitted, particulate filter respirator complying with an approved standard if

a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working

limits of the selected respirator. Recommended: Dust respirator.

Personal protective equipment (Pictograms)



Section 9. Physical and chemical properties

Appearance

(flammable) limits

Physical state Solid. [Powder.]

Color Beige.

Odor Aromatic. [Slight]
Odor threshold Not available.

pH 7 to 10.5 [Conc. (% w/w): 1%]

Melting point Not available. **Boiling point** Not available. **Flash point** Not available. **Burning time** Not available. **Burning rate** Not available. **Evaporation rate** Not available. Flammability (solid, gas) Not available. Lower and upper explosive Not available.

Section 9. Physical and chemical properties

Vapor pressureNot available.Vapor densityNot available.

Density 0.7 g/cm³ [25°C (77°F)]

Relative density 0.7

Solubility Easily soluble in the following materials: cold water and hot water.

Solubility in water Not available.

Partition coefficient: n- Not available.

octanol/water

Auto-ignition temperature

Decomposition temperature

SADT

Not available.

Not available.

Not available.

Not available.

Aerosol product

Section 10. Stability and reactivity

ReactivityNo specific test data related to reactivity available for this product or its ingredients.

Chemical stability The product is stable.

Possibility of hazardous reactions

Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid

Avoid the creation of dust when handling and avoid all possible sources of ignition (spark or flame). Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Prevent dust accumulation.

Incompatible materials

Reactive or incompatible with the following materials: oxidizing materials

Hazardous decomposition

products

Under normal conditions of storage and use, hazardous decomposition products should

not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
DARVAN® 670	LD50 Oral	Rat	>2000 mg/kg Based on tests of similar materials	-

Irritation/Corrosion

Not available.

Validation date : 3/7/2019 Date of previous issue : 11/27/2017 7/13

Section 11. Toxicological information

Conclusion/Summary

Eyes Slight irritant. **Respiratory** Slight irritant.

Sensitization

Not available.

Mutagenicity

Not available.

Carcinogenicity

Not available.

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Information on the likely

routes of exposure

Routes of entry anticipated: Oral, Inhalation.

Potential acute health effects

Exposure to airborne concentrations above statutory or recommended exposure

limits may cause irritation of the eyes.

Inhalation Exposure to airborne concentrations above statutory or recommended exposure

limits may cause irritation of the nose, throat and lungs.

Skin contact No known significant effects or critical hazards.

Ingestion May be harmful if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact Adverse symptoms may include the following:

irritation redness

Inhalation Adverse symptoms may include the following:

respiratory tract irritation

coughing

Validation date : 3/7/2019 Date of previous issue : 11/27/2017 8/13

Section 11. Toxicological information

Skin contactNo specific data.IngestionNo specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate Not available.

effects

Potential delayed effects Not available.

Long term exposure

Potential immediate Not available.

effects

Potential delayed effects Not available.

Potential chronic health effects

Not available.

General Repeated or prolonged inhalation of dust may lead to chronic respiratory irritation.

CarcinogenicityNo known significant effects or critical hazards.MutagenicityNo known significant effects or critical hazards.TeratogenicityNo known significant effects or critical hazards.Developmental effectsNo known significant effects or critical hazards.Fertility effectsNo known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Not available.

Other information Not available.

Section 12. Ecological information

Toxicity

Not available.

Persistence and degradability

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
DARVAN® 670	-	-	Not readily

Bioaccumulative potential

Not available.

Mobility in soil

Soil/water partition Not available. coefficient (Koc)

Validation date : 3/7/2019 Date of previous issue : 11/27/2017 9/13

Section 12. Ecological information

Other adverse effects

No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Section 14. Transport information

Regulatory information	UN number	Proper shipping name	Classes	PG*	Label	Additional information
DOT Classification	Not regulated.	-	-	-		-
TDG Classification	Not regulated.	-	-	-		-
ADR/RID Class	Not regulated.	-	-	-		-
IMDG Class	Not regulated.	-	-	-		-
IATA-DGR Class	Not regulated.	-	-	-		-

PG*: Packing group

Section 15. Regulatory information

United States inventory (TSCA 8b)

All components are listed or exempted.

U.S. Federal regulations

TSCA 8(a) PAIR: Naphthalene

TSCA 8(a) CDR Exempt/Partial exemption: Not determined

Clean Water Act (CWA) 307: Naphthalene

Clean Water Act (CWA) 311: Formaldehyde; Quinoline; Naphthalene

SARA 302/304

Composition/information on ingredients

 Validation date
 : 3/7/2019
 Date of previous issue
 : 11/27/2017
 10/13

Section 15. Regulatory information

			SARA 302 TPQ		SARA 304 RQ	
Name	%	EHS	(lbs)	(gallons)	(lbs)	(gallons)
Formaldehyde	<0.1	Yes.	500	73.6	100	14.7

SARA 304 RQ 111111.1 lbs / 50444.4 kg

SARA 311/312

Classification COMBUSTIBLE DUSTS

Composition/information on ingredients

No products were found.

State regulations

Massachusetts The following components are listed: SODIUM SULFATE (SOLUTION)

New York None of the components are listed.

New Jersey None of the components are listed.

Pennsylvania The following components are listed: SODIUM SULFATE (SOLUTION)

California Prop. 65

WARNING: This product can expose you to chemicals including Quinoline and its strong acid salts, Formaldehyde, Naphthalene, which are known to the State of

California to cause cancer. For more information go to www.P65Warnings.ca.gov.

Ingredient name	_	Maximum acceptable dosage level
Quinoline and its strong acid salts Formaldehyde Naphthalene	- Yes. Yes.	- -


International regulations

Australia inventory (AICS) All components are listed or exempted. Canada inventory All components are listed or exempted. China inventory (IECSC) All components are listed or exempted. **Europe inventory** All components are listed or exempted. Japan inventory (ENCS) All components are listed or exempted. Korea inventory (KECI) All components are listed or exempted. All components are listed or exempted. **New Zealand Inventory of Chemicals** (NZIoC) **Philippines inventory (PICCS)** All components are listed or exempted. **Taiwan Chemical Substances** All components are listed or exempted. **Inventory (TCSI)**

Validation date : 3/7/2019 Date of previous issue : 11/27/2017 11/13

Section 16. Other information

Hazardous Material Identification System (U.S.A.)



Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

National Fire Protection Association (U.S.A.)



Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

History

Date of printing3/7/2019Validation date3/7/2019Date of previous issue11/27/2017

Version 4

Key to abbreviations

ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973

as modified by the Protocol of 1978. ("Marpol" = marine pollution)

UN = United Nations

References Not available.

Information contact Vanderbilt Global Services, LLC

Corporate Risk Management

1-203-295-2143

Visit www.vanderbiltminerals.com for more information.

Notice to reader

Information presented herein has been compiled from sources considered to be dependable and is accurate and reliable to the best of our knowledge and belief but is not guaranteed to be so. Nothing herein is to be construed as recommending any practice or any product in violation of any patent or in violation of any law or regulation. It is the user's responsibility to determine for himself the suitability of any material for a specific purpose and to adopt such safety precautions as may be necessary. We make no warranty as to the results to be obtained in using any material and, since conditions of use are not under our control, we must necessarily disclaim all liability with respect to the use of any material supplied by us.

Validation date : 3/7/2019 Date of previous issue : 11/27/2017 12/13

Section 16. Other information

 Validation date
 : 3/7/2019
 Date of previous issue
 : 11/27/2017
 13/13